

Label / Receipt Printer

MP-B21L

Measuring
InstrumentPDA/
Smart Device

Barcode

Portable
PrinterMedical
Equipment

Label

Food Labels



Barcode Labels



Medical Healthcare Labels



Ultra Small Mobile Label Printer

- Compact & Light Weight
- Drop rating: 1.8m(6feet), IP rating:IP54
- Printing Speed: 153mm/sec max
- SII Layout Editor: Label designing application (iOS, Android & Windows)
- SII URL Print Agent: PDF print application (iOS & Android)
- Simple Operation & Stylish Design
- Option Cradle for Charging

Model		MP-B21L
Printing	Method	Thermal line dot printing
	Number of dots/line	384
	Resolution(dots/mm)	8
	Paper width(mm)	58 ^{*1}
	Printing width(mm)	48
	Printing speed(mm/sec) max	153 (6inch)
	Outside diameter of paper roll(mm)max	Φ51
	Character matrix(HxW dots)	24 X 12, 24 X 24, 16 X 8, 16 X 16
	Character dimensions(HxW mm)	3.0 X 1.5, 3.0 X 3.0, 2.0 X 1.0, 2.0 X 2.0
Type of paper		Roll paper, Label roll paper
Media sensor		Mark sensor, Gap sensor
Character type		Code page(17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Barcode		UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar, Aztec Code
Power supply		Li-Ion Battery
Communication interface		USB, Bluetooth®, W-LAN ^{*2}
Command		ESC/POS™conformity
Cutting method		Tear bar
Drop rating		1.8m ^{*3}
IP rating		IP54 ^{*3}
Operating Temperature(°C)		-20 to 55
Service life: Abrasion resistance(km)		50 ^{*4}
Dimensions (WxDxHmm)		90 X 126 X 58 ^{*5}
Mass (g)		370 ^{*6}
Standard		FCC, CE, VCCI
bundled items		AC dapter, Battery, USB cable, Belt crip, Sample roll paper
Options		Cradle for charging, Single battery charger, Quad battery charger, Car charger, Strap, Carrying case
Software		Printer driver/SDK, OPOS driver, POS for .NET, Android™SDK, Xamarin SDK, URL Print Agent, Layout Editor

^{*1} Please inquire about support for narrow paper. ^{*2} Selected model. ^{*3} This number is test result based on SII procedures, not guaranteed value.

^{*4} Use recommended thermal papers. ^{*5} Excluding protrusion ^{*6} with battery, without paper roll

ESC/POS™: Registered trademark of SEIKO EPSON CORP. Windows® is the registered trademark of Microsoft Corporation(USA). Android™ is a trademark of Google Inc. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.



Seiko Instruments Inc.
Print System Div.
8, Nakase 1-chome, Mihama-ku
Chiba-shi, Chiba 261-8507, Japan
Telephone:+81-43-211-1106 Facsimile:+81-43-211-8037
<http://www.sii.co.jp/sps/eg/>

Seiko Instruments U.S.A., Inc.
21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.
Telephone:+1-310-517-7778 Facsimile:+1-310-517-7779
<https://sii-thermalprinters.com>

Seiko Instruments GmbH
Siemensstrasse 9 D-63263 Neu-Isenburg, Germany
Telephone:+49-6102-297-0 Facsimile:+49-6102-297-222
E-mail : info@seiko-instruments.de
<https://www.seiko-instruments.de/>