

Model name	NP-2511D-4	NP-3511D-4
Print method	Direct line thermal dot	
Print speed	300mm/sec. (at max.)	
Resolution	8 dots/mm (203dpi)	
Number of dots/line	448 dots	640 dots
Print width	56mm(at max.)	80mm(at max.)
Paper width	52mm, 54mm, 58mm, 60mm	76mm, 80mm, 83mm
Character	International, English, Greek, Polish, Russian, Scandinavian, Turkish, Arabic, Thai, Hebrew, Chinese, Taiwanese, Japanese, Korean	
Barcode	UPC-A, UPC-E, JAN-13 (EAN-13), JAN-8 (EAN-8), CODE39, ITF, CODABAR, CODE128, CODE93, ISBN, Industrial 2 of 5, Matrix 2 of 5, NEC Matrix, Customer barcode, MSI Code, EAN-128 (GS1-128), GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, PDF417, QR code model 2, Split QR codes model 2, Micro QR code, Aztec Code, Micro PDF417, MaxiCode, DataMatrix, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked EAN-8 Composite, EAN13 Composite, UPC-A Composite, UPC-E Composite, GS1-128 Composite, GS1 DataBar Omnidirectional Composite, GS1 DataBar Truncated Composite, GS1 DataBar Limited Composite	
Interface	USB (V2.0 full speed) and Serial (RS232C)	
Cutter	Full cut and partial cut by the command	
Operating voltage	DC 24V	
External dimensions (approx.)	106.0(W) x 150.4(D) x 85.7(H) mm	127.0(W) x 150.4(D) x 85.7(H) mm